



1000

Beton: B30

Stal: A-I St3S>
A-III 34GS

1. Rozmieszczenie strzemion przy oparciu dodatkowe, belki pokazano na Detalu "A".

Specyfikacja zbrojenia									
Element	Poz.	Szkiełko przęta	φ	Długość L mm	Łość w m	Łość w t	n x L	Ciężar prętów kg	Ciężar ogólny kg
Bh-11, szt.1	35		8	1480	208.208	307,8			899,7 kg
	42		20	6570	20	131,4			
	43		20	4140	10	41,4			
	44		20	6970	15	104,6			
	45		20	4030	3	12,1			
	46		20	4830	3	14,5			
Bh-10, szt.2	47		20	2570	2	5,1			319,3 kg
	48		20	2970	2	5,9			
Bh-7, szt.2	1		6	1080	16	17,3		3,8	319,3 kg
	7		16	3920	2	7,8		28,1	
	6		16	3320	3	10,0			
	4		6	1080	11	22	23,8	5,3	
	13		16	2850	2	4	11,4		
	23		16	2250	3	6	13,5		
Bh-6, szt.4	26		8	1380	28	56,77		30,5	199,3 kg
	23		16	5670	2	4	22,7	35,9	
	26		20	4970	3	19,3		132,9	
	1		20	6000	2	4	24,0		
	12		6	1080	12	96	103,7	23,0	
	1		16	3130	2	16	50,1	175,0	
Bh-4, szt.4	22		16	2530	3	24	60,7		108,3 kg
	22		8	1380	31	42,8		16,9	
	25		20	6120	2	12	12,2	19,3	
	28		20	5420	3	3	16,3		
	25		20	6450	2	2	12,9	72,1	
	21		8	1380	36	49	49,7	19,6	
Bh-2, szt.2	21		16	7170	2	2	14,3	22,6	127,2 kg
	27		20	6470	3	3	19,4		
	24		20	7500	2	2	15,0	85,0	
Bh-1, szt.1	2		6	1080	22	22	23,7		40,5 kg
	11		16	4820	2	2	9,6	35,2	
Bh-29, szt.1	1		6	1080	16	16	17,3		40,5 kg
	11		16	3920	2	2	7,8	28,1	
	1		16	3320	3	3	10,0		
Bh-26, szt.4	1		6	1080	12	12	23,8	5,3	199,3 kg
	17		16	2850	2	4	11,4		
	18		16	2250	3	6	13,5		
Bh-27, szt.1	1		6	1080	21	21	22,7		319,3 kg
	8		16	3920	2	2	7,8	28,1	
	17		16	3320	3	3	10,0		
Bh-26, szt.4	67		8	1380	28	28	56,77		758,5 kg
	68		16	5670	2	4	22,7	35,9	
	69		20	4970	3	3	19,3	132,9	
	70		20	6000	1	4	24,0		
	71		20	5420	1	1	21,7		
	72		20	7060	1	1	28,2		
	73		20	6990	1	1	28,0		
	74		20	9300	1	1	37,2		
	75		16	2000	1	1	8,0	12,6	
	60		8	1580	51	204	322,3	127,3	
Bh-25, szt.1	40		6	1080	26	26	30,4	31,2	302,8 kg
	41		16	5560	2	10	55,6	87,8	
	40		20	4960	3	15	74,4	183,8	
Ba-24, szt.1	61		8	1380	60	60	82,8		251,2 kg
	62		20	11990	2	2	24,0		
	63		20	12000	3	3	36,0		
	64		20	4200	2	2	8,4		
	65		20	11100	3	3	33,3		
	66		16	4550	1	1	4,6		
Ba-23, szt.1	30		16	3750	1	1	3,8	13,3	495,0 kg
	31		8	1680	66	66	244,5	175,2	
	32		16	9400	3	12	112,8	178,2	
	33		20	9900	1	1	39,6		
	34		20	9900	1	1	39,6	444,6	
	35		20	8400	3	12	100,8		
Ba-22, szt.1	36		8	1480	50	50	74,0	29,2	146,4 kg
	37		16	7150	3	3	21,5	34,0	
	38		20	7560	1	1	7,6		
	39		20	7560	1	1	7,6	83,2	
	40		20	6150	3	3	18,5		
	49		20	9320	4	4	37,3		
Ba-20, szt.1	50		20	7030	16	16	112,5		945,1 kg
	51		20	3700	1	1	3,7		
	52		20	3300	1	1	3,3		
	53		20	5110	4	4	20,4		
	54		20	4310	4	4	17,2		
	55		20	3180	1	1	3,2		
	56		20	2780	1	1	2,8		
	57		16	6710	4	4	26,8		
	58		16	7400	16	16	118,4	256,6	
	60		16	3510	4	4	17,2		
	60		8	1580	310	310	489,8	193,5	

[illegible]